

PLUMBING/FIRE PROTECTION

A. Fixtures:

1. Flush Valves*: **Sloan** Manual Exposed Flushometer with Technical Concept Clamp on Auto Flush Part #401805.
2. Toilets: **American Standard** floor mount.
3. Urinals: Water less **Borrego™ Model # 2103**, Vitreous China No-Flush Urinal
4. Drinking Fountains: **Haws #1119.14A for hi/lo and 1109.14 for single application**
5. Sink Faucets*: **Chicago Faucet.**
6. Water Closet Seats: **Olsonite, Beneke, Church or Sperzel.**
7. Sinks: **Vitreous China Fixtures: CS20.**
8. Rest Room Faucets: **Touch-free Speakman Sensorflo Part# S-9010.**

B. Piping:

1. No. 1 1/4" piping to be used.

C. Valves:

1. All shut off valve less than 4" shall be ball valves.
2. All water to restrooms shall have room isolation valves.

D. Water Heaters: (Electric Only)

**A. O. Smith
Rudd
Rheem
Hoyt**

E. Indirect Water Heater:

**Amtrol Boilermate Premier Series with
SMARTCONTROL. Model: WHSCDW
(60 gallon and above)**

F. Miscellaneous:

1. Hose bibs shall be installed on the exterior of buildings at 120 feet apart.
2. Hose bibs and floor drain required in restrooms and lockers rooms.

G. Fire Protection System: TBD

* Sole Source